

Art. Nr.	Material Grundkörper	Öffnungswinkel			Öffnungswinkel			Öffnungswinkel			Öffnungswinkel			Öffnungswinkel			Öffnungswinkel		
		Haltearm Position 1			Haltearm Position 2			Haltearm ohne Anschlag			Griff Position 1			Griff Position 2			Griff ohne Anschlag		
101 130 460	Stahl	130°			-			160°			90°			-			100°		
101 130 461	Stahl	95°			-			185°			65°			-			105°		
101 130 462	Stahl	95°			-			185°			75°			-			110°		
101 130 463	Stahl	95°			125°			160°			70°			85°			100°		
101 130 464	Stahl	90°			120°			180°			70°			80°			110°		
101 130 465	Stahl	90°			125°			180°			70°			85°			110°		
101 130 466	Stahl	90°			120°			180°			65°			80°			110°		

Art. Nr.	Material Grundkörper	A	A1	A2	A3	B	B1	B3	B4	C	C1	D	H	L	L1	M	Handkraft	Haltekraft	Haltekraft	Spannkraft	Spannkraft
																	FH	F1	F2	F3	F4
																	N	N	N	N	N
101 130 460	Stahl	16	25	5	-	24	34	5,5	-	16	9	4,4	94	57	32	M5x35	80	700	1100	500	750
101 130 461	Stahl	16	29	6	14	24	34	5,5	17,5	22	9,5	4,8	98	67	38	M5x35	80	700	1000	500	800
101 130 462	Stahl	12,7	27	7	-	27	38	6,4	-	23	11	5,1	121	70	43	M6x50	120	1350	1650	800	1050
101 130 463	Stahl	19	35	8	-	32	45	8,8	-	32	17,5	7,1	175	110	75	M8x60	190	1000	2800	900	1700
101 130 464	Stahl	32	50	9	-	45	64	10,6	-	43	22	8,3	220	145	95	M10x80	230	2200	4500	1400	3000
101 130 465	Stahl	32	53	10	-	45	64	12,7	-	51	25	8,7	228	177	124	M12x100	260	3200	7000	1400	3000
101 130 466	Stahl	51	76	12,5	-	70	95	16,5	-	84	32	12,3	312	232	156	M16x150	290	3000	8000	1800	3900