

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Page 1/8

Printing date 20.06.2017

Revision: 20.06.2017

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· Trade name: **STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

· Article number: 104409040

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** Adhesives

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Stankovsky Industrieprodukte Handels GmbH  
Flachenuergutstraße 8  
4020 Linz  
AUSTRIA  
Tel.: +43 732 221877  
e-Mail: office@staloc.com  
www.staloc.com

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** EU emergency phone number: 112

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Eye Dam. 1      H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2   H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Skin Sens. 1      H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05



GHS07



GHS09

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

Trade name: **STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 1)

· **Signal word** Danger· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)  
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine

· **Hazard statements**

H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves / eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<25%
CAS: 90-72-2 EINECS: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	$\leq$ 10%
CAS: 68082-29-1	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information:** Immediately remove any clothing soiled by the product.· **After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:** If symptoms persist consult doctor.· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

**Trade name: STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 2)

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:** No special measures required.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:** No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

**Trade name: STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Pasty
· <b>Colour:</b>	Grey
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	Undetermined.

· **Flash point:** >200 °C

· **Flammability (solid, gas):** Not determined.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

Trade name: **STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 4)

· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapour pressure:</b>	Not applicable.
· <b>Density at 20 °C:</b>	1.85 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not applicable.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Insoluble.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	100.0 %
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

**Trade name: STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 5)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Must not reach sewage water or drainage ditch undiluted or unneutralised.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UN3077
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700), Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)
· <b>IMDG</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700), Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine), MARINE POLLUTANT
· <b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700), Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine)

(Contd. on page 7)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 20.06.2017

Revision: 20.06.2017

**Trade name: STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 6)

<p>· <b>14.3 Transport hazard class(es)</b></p> <p>· <b>ADR, IMDG, IATA</b></p>	
	
<p>· <b>Class</b></p> <p>· <b>Label</b></p>	<p>9 Miscellaneous dangerous substances and articles.</p> <p>9</p>
<p>· <b>14.4 Packing group</b></p> <p>· <b>ADR, IMDG, IATA</b></p>	
	<p>III</p>
<p>· <b>14.5 Environmental hazards:</b></p> <p>· <b>Marine pollutant:</b></p> <p>· <b>Special marking (ADR):</b></p> <p>· <b>Special marking (IATA):</b></p>	
	<p>Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <math>\leq 700</math>)</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>
<p>· <b>14.6 Special precautions for user</b></p> <p>· <b>Danger code (Kemler):</b></p> <p>· <b>EMS Number:</b></p> <p>· <b>Stowage Category</b></p> <p>· <b>Stowage Code</b></p>	
	<p>Warning: Miscellaneous dangerous substances and articles.</p> <p>90</p> <p>F-A,S-F</p> <p>A</p> <p>SW23 When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9.</p>
<p>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></p>	
	<p>Not applicable.</p>
<p>· <b>Transport/Additional information:</b></p> <p>· <b>ADR</b></p> <p>· <b>Limited quantities (LQ)</b></p> <p>· <b>Excepted quantities (EQ)</b></p> <p>· <b>Transport category</b></p>	
	<p>5 kg</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 g</p> <p>Maximum net quantity per outer packaging: 1000 g</p> <p>3</p>
<p>· <b>IMDG</b></p> <p>· <b>Limited quantities (LQ)</b></p> <p>· <b>Excepted quantities (EQ)</b></p>	
	<p>5 kg</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 g</p> <p>Maximum net quantity per outer packaging: 1000 g</p>
<p>· <b>UN "Model Regulation":</b></p>	
	<p>UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <math>\leq 700</math>), FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE), 9, III</p>

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.06.2017

Revision: 20.06.2017

**Trade name: STALOC K-818 Power Repair Steel Stick, 56 g / 115 g**

(Contd. of page 7)

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H302 Harmful if swallowed.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.
  - H319 Causes serious eye irritation.
  - H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Product safety department
- **Contact:** Hr Stankovsky
- **Abbreviations and acronyms:**
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Acute Tox. 4: Acute toxicity . Category 4
  - Skin Irrit. 2: Skin corrosion/irritation . Category 2
  - Eye Dam. 1: Serious eye damage/eye irritation . Category 1
  - Eye Irrit. 2: Serious eye damage/eye irritation . Category 2
  - Skin Sens. 1: Skin sensitisation . Category 1
  - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2