

DUPLI-COLOR PRIMA COLOR PRIMER

Ord.-no.: look at ordering information



Technical Information

This Primer for universal use grants the excellent adhesion of the subsequent top coating with DUPLI-COLOR PRIMA COLORS, nitro-combi or acrylic spray paints. Suitable for the most surfaces, such as ceramics, eternite, carton, of course even on wood and metal.

Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Very good flow, smooth surface
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Grants the economical application of the top coat
- For indoor and outdoor applications

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: grey
- Smell: Characteristic
- Efficiency:
 - ◊ 400 ML – 0,8 m²
 - ◊ 500 ML – 1.25 m²
 - ◊ 600 ML – 1.5 m²
- Dry to touch: 40 min
- Dust dry: 12 min
- Completely dry: 2 h
- Overcoatable: 2 h
- Surfaces: metal, wood, ceramics, stone, carton und much more.
- Vapour pressure: 8300/20 bar
- Temperature Resistance: – 110 °C
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 500 ML
 - ◊ 600 ML

How to use

- Usage Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust, sand the surface and apply a layer of primer. After drying, sand the base layer (grain 600).
- Treatment The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter. Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.
- Tips for spray painting Protect the object and the surrounding area from spray mist. Temperature should range between +10°C and +25°C, max. air humidity 60 %. Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of January 12, 2023 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com