



# **Dissolver SP**

Revision: 5/09/2018 Page 1 from 2

### **Technical data**

Basis	Solvent mixture
Consistancy	Liquid
Density**	Ca. 0,81 g/ml
Flashpoint	Ca25 °C
Boiling point	Ca. +70°C
Consumption (*)	100 - 300 ml/m², each side
Application temperature	5 °C → 35 °C

<sup>\*</sup> These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

## **Product description**

Dissolver SP is a universal, colorless, cleaner, thinner and remover. Cleans all tooling: brushes, spatulas, guns, ... as well as stains of adhesive and redundant adhesive.

### **Properties**

- Ready for use
- Fast-working
- Universal applications
- Cleans substrates meant for adhesion
- For breaking of adhesive bonds
- Cleaner for tooling
- With special mount for cleaning hose and gun of canister adhesives.

## **Applications**

- Transparent solvent mixture suitable for removing fresh glue stains and cleans brushes, palette knives and glue spatulas.
- For breaking of adhesive bonds
- Voor cleaning and degreasing of surface before adhesion.

# **Packaging**

Colour: transparent Packaging: 500ml aerosol

#### Shelf life

At least 24 months in original, unopened packaging at a cool and dry storage place, between +5°C and +25°C.

# **Application method**

Application method: Spray cleaner: Put the spray tip on the aerosol. Aim the aerosol and spray. Give the product some time to do it's job, then remove using a dry cloth or spatula. Cleaning nozzles of adhesive guns: Put the spray top on the aerosol. Aim the aerosol and spray. Give the product some time to do it's job, then remove using a soft brush. Cleaning the gun and hose of a canister adhesive: Make sure the canister and hose are closed. Dismount the hose from the canister. Screw the cleaning adapter on the hose. Put the Dissolver SP on the adapter. Spray until a clear liquid leaves the gun (in case nothing leaves the gun, give it some time to affect and try again). Then remove the dissolver from the adapter and empty the hose and gun. Remove the adapter and the hose and gun are ready to reuse.

# **Health- and Safety Recommendations**

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Do not smoke. For more information see Material Safety Data Sheet.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com





# **Dissolver SP**

Revision: 5/09/2018 Page 2 from 2

#### Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.
- Not suitable on some plastics and polystyrene (PS).

### Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

Soudal NV Tel: +32 (0)14-42.42.31 Everdongenlaan 18 - 20 Fax: +32 (0)14-42.65.14