

Tragfähigkeitstabelle

Bandabstand (mm)	K6100 - 10,5 Kg - Nr. 2 Türbänder							
	850		10,5	10,5	10,5	10,5	10,5	9,0
	750		10,5	10,5	10,5	10,5	9,2	7,9
	650		10,5	10,5	10,5	9,5	7,9	6,8
	550		10,5	10,5	10,5	8,0	6,7	5,7
	450		10,5	10,5	8,1	6,5	5,4	
	350		10,5	8,2	6,1	4,9		
	820	10,5						
		600	200	300	400	500	600	700
Türbreite (mm)								

Bandabstand (mm)	K6100 - 14 Kg - Nr. 3 Türbänder							
	1350		14,0	14,0	14,0	14,0	14,0	12,9
	1250		14,0	14,0	14,0	14,0	14,0	12,0
	1150		14,0	14,0	14,0	14,0	13,0	11,1
	1050		14,0	14,0	14,0	14,0	12,0	10,3
	950		14,0	14,0	14,0	13,2	11,0	9,4
	850		14,0	14,0	14,0	12,0	10,5	9,0
	1320	14						
		600	200	300	400	500	600	700
Türbreite (mm)								

Bandabstand (mm)	K6100 - 19 Kg - Nr. 4 Türbänder							
	1850		19,0	19,0	19,0	19,0	19,0	16,3
	1750		19,0	19,0	19,0	19,0	18,1	15,5
	1650		19,0	19,0	19,0	19,0	17,1	14,7
	1550		19,0	19,0	19,0	19,0	16,2	13,8
	1450		19,0	19,0	19,0	18,2	15,2	13,0
	1350		19,0	19,0	19,0	17,1	14,0	12,9
	1820	19						
		600	200	300	400	500	600	700
Türbreite (mm)								